

WiRē Rapid Assessment Scoring Guide

	Risk attribute	Response categories	Attribute weight	Category score
Home ignition potential	Roof	Tile, metal, or asphalt shingles	30%	0
		Wood (shake shingles)		300
	Siding	Stucco, cement, brick, stone, or other noncombustible siding	7%	0
		Log or heavy timbers		35
		Wood or vinyl siding		70
	Combustible attachments	No combustible attachments	10%	0
		Combustible attachments present		100
	Distance to adjacent homes	More than 100'	20%	0
		30' - 100'		50
		10' - 29'		100
		Less than 10'		200

	Risk attribute	Response categories	Attribute weight	Category score
Defensible space	Distance to overgrown vegetation (0' - 100')	More than 100'	10%	0
		30' - 100'		50
		5' - 29'		75
		Less than 5'		100
Distance to other combustibles (non-vegetation)	More than 30' or no combustible items	8%	0	
	5' - 30'		40	
	Less than 5'		80	

Risk rating	Low	20	250
	Moderate	251	325
	High	326	455
	Very high	456	540
	Extreme	541	1000

	Risk attribute	Response categories	Attribute weight	Category score
Background conditions	Distance to dangerous topography	More than 150'	5%	0
		50' - 150'		25
		Less than 50'		50
	Slope	Gentle: Less than 20%	2%	0
		Moderate: 20% - 45%		10
		Steep: Greater than 45%		20
Adjacent fuels (100' - 150')	Light	4%	10	
	Medium		20	
	Dense		40	

	Risk attribute	Response categories	Attribute weight	Category score
Address posting		Fully meets standard	1%	0
		Visible, but does not meet all standards		5
		Not posted/visible from the primary road		10
Ingress/Egress		Two or more roads in/out	1%	0
		One road in/out		10
Driveway clearance		Meets both standards (height and width)	1%	0
		Meets one, but not both, standards (height or width)		5
		Does not meet either standard (height or width)		10
Driveway length		Less than 150' long	1%	0
		150' or more with "adequate" turnaround		5
		150' or more without "adequate" turnaround		10